



ASSA ABLOY

ASSA ABLOY, the global leader
in door opening solutions

Ensure Better Performing Buildings with CURRIES Weatherized Doors and Frames

MAY, 2011

Thermal Break Hollow Metal Frames

Stops frost from forming on
the inside of an opening.

CURRISeal Frames

Prohibits the loss of heat
from escaping between the
door and frame.

Trio-E Doors

Steel stiffened polyurethane
core doors have outstanding
thermal properties to provide
complete resistance to the
harshest cold and winds that
Mother Nature can create.



*CURRIES door and frame pictured above
includes closer and exit device from
Sargent and hinges from McKinney.*




Approximately 40% of all energy leakage comes from the building envelope,*
this includes exterior doorways.

Finding ways to cut energy cost is a smart and environmentally wise decision. With the rising cost of energy any reduction in the heating or cooling of a building affects the bottom line of a company. This same energy reduction is also an eco-friendly choice. Making these wise choices is becoming a necessity for surviving in this difficult market. Look to CURRIES for help in making the right choice in your openings solutions.

** Tony Woods, Air Tight Buildings, 2005*

Log onto www.curries.com to learn more about our weatherized solutions.

1502 12th Street NW
Mason City • IA 50401
Phone: 641-423-1334
Fax: 641-424-8305



Trio-E Doors

The CURRIES Trio-E is a new patent pending design that delivers superior insulated values and strength plus, provides aesthetic qualities desired in today's commercial building applications. The "E" is for energy efficiency and Trio-E has the lowest U-Factor (0.29) for a steel stiffened door in the market today.

U-Factor		R-Factor	
ASTM C1363	Operable – .029	ASTM C1363	Operable – 3.4
ASTM C518	Calculated – 0.09	ASTM C518	Calculated – 11.0
Air Infiltration			
ASTM E283	CFM/SQ FT – 0.03		
	CFM/LN FT – 0.04		

CURRISeal Frames

CURRISeal Frames have been designed to satisfy the need for energy conservation in buildings as well as openings to conform to life safety codes.

The heart of the CURRISeal system is the compression air seal gasket that fits tightly into a kerf formed into the stop area of the frame. The non-vinyl exterior case of the air seal gasket is unaffected by paint or ultraviolet light and has been cycle tested to one million openings and closings with a hollow metal door without severe damage or failure of the air seal gasket.

CURRISeal frames have been tested in accordance with UL 1784, Air Leakage Tests of door assemblies and ASTM E283, Standard Test Methods for rate of air leakage through exterior windows, curtain walls and doors. CURRISeal frames meet the requirements specified in ANSI/NFPA 105, recommended practice for the Installation of smoke-control door assemblies, and UBC 7.210, test standard for smoke and draft control assemblies of the International Conference of Building Officials.

Thermal Break Hollow Metal Frames

Heat loss is greatly reduced — frost and condensation on the interior door frame face are successfully combatted — with the CURRIES Thermal-Break Hollow Metal Door Frame.

This is accomplished by means of a strategically placed gasket that provides a positive thermal-break within the steel frame and thereby delivers maximum protection against cold penetration.

Mullions used in CURRIES sidelite and borrowed lite frames feature the same basic Thermal-Break design as CURRIES regular Thermal-Break Frames.

Top quality, superior-performance CURRIES Thermal-Break Hollow Metal frames are available knocked down for masonry and drywall construction. The frame is manufactured out of **16 gauge galvanealed steel**; jamb depths ranging from 5-1/2" through 12-3/4" at 1/8" increments.

ALSO FOR TRANSOMS, SIDELITES AND BORROWED LITES. Available in **16 gauge, galvanealed steel**; equal rabet; various jamb depths.