

StormPro[®] Multi-Point Exit Tornado Resistant Assembly UL Classified to ICC500 - 2014

Available Sizes:

- Pairs 6'0" x 7'0" minimum to 8'0" x 8'0" maximum
- Singles 3'0" x 7'0" minimum to 4'0" x 8'0" maximum

Frame Type:

- StormPro 14 gauge frame single, 4" depth thru 14"
- StormPro 14 gauge frame pairs, 5-1/2" depth thru 14"
- 4" head option
- Masonry or EO anchors

Door Type:

- 16 gauge StormPro door with polystyrene core and liner (Honeycomb core if fire rated)

Hardware Options:

- Multi-Point Exit Device: Corbin Russwin FE5400S
- Hardware Mullion: Corbin Russwin FE707A Series or FE708A Series

Hinges:

- McKINNEY SP butt hinges
- McKINNEY MCK-HG305 continuous hinges
- MARKAR HG-305 continuous hinges

Accessories:

- Door closers, perimeter seals, electronic power transfer, and door position switches are also available

1502 12th Street NW
Mason City, IA 50401
Phone: 641-423-1334
Fax: 641-424-8305
www.curries.com



CURRIES StormPro[®] Multi-Point Exit assemblies include paired openings 6'0" x 7'0" minimum through 8'0" x 8'0" maximum with a required mullion. Single openings are available from 3'0" x 7'0" minimum to 4'0" x 8'0" maximum. These StormPro[®] assemblies give end-users another option for creating highly functional safe rooms with easy means of egress.

The StormPro[®] Multi-Point Exit assembly helps shield occupants in a safe room from flying debris. The assemblies are UL classified to ICC-500 2014 and comply with FEMA P320 and P361. StormPro[®] doors are also fire rated up to and including 3 hours. As with all StormPro[®] products, the third party Underwriters Laboratory certification labels are applied to each assembly.

Visit www.curries.com or contact an ASSA ABLOY Door Security Solutions representative for more information.