



**TEST STANDARDS**

ICC	500-2014
FEMA	361-2015

**FRAMES**

<b>DESCRIPTION</b>	3F AND COMMUNICATING - SEE NOTE BELOW
<b>LABEL</b>	UL WINDSTORM LABEL REQUIRED MAY BE UL FIRE RATED UP TO 180 MINUTES
<b>JAMB DEPTH</b>	4" MINIMUM - SINGLE RABBET; 4-1/4" MIN. UNEQUAL RABBET; 5-5/8" MIN. EQUAL RABBET, 14" MAXIMUM
<b>PROFILE TYPE</b>	M, G
<b>STEEL GAUGE</b>	14
<b>STEEL TYPE</b>	COLD ROLLED, GALVANEALD
<b>CONSTRUCTION</b>	KD OR WELDED AT FACTORY
<b>HAND</b>	IN SWING OR OUT SWING
<b>ANCHORS</b>	<b>JAMB</b> MASONRY T, MASONRY WIRE, WPS, OR WEWA <b>HEAD OF 3F</b> WPS, WEWA, REQUIRED IN HEAD AND SILL
<b>OVERALL WIDTH</b>	3'4" MIN, 4'4" MAX
<b>OVERALL HEIGHT</b>	7'2" MIN, 8'4" MAX
<b>DOUBLE OPENING</b>	ALLOWED
<b>4" FACE HEAD</b>	ALLOWED
<b>MFG LOCATIONS</b>	ANY SDI MANUFACTURER
<b>STRIKES</b>	E1 IN JAMB AND G20 IN HEAD
<b>SILENCERS</b>	ALLOWED
<b>NOTE</b>	JAMB DEPTH FOR COMMUNICATING FRAME DICTATED BY CLEARANCE REQUIRED FOR TRIM ON BOTH DOORS. BOTH DOORS MUST BE ABLE TO BE FULLY CLOSED AND LATCHED

**DOORS**

<b>FACE TYPE</b>	FLUSH
<b>LABEL</b>	UL WINDSTORM LABEL REQUIRED MAY BE UL FIRE RATED UP TO 180 MINUTES
<b>DOOR SERIES</b>	707 (POLYURETHANE, HONEYCOMB FOR FIRE RATED ONLY)
<b>DOOR EDGE</b>	CONTINUOUSLY WELDED
<b>STEEL GAUGE</b>	14 GAUGE
<b>STEEL TYPE</b>	COLD ROLLED, GALVANEALD
<b>BEVEL</b>	A
<b>TOP CAP</b>	REQUIRED
<b>HAND</b>	IN SWING OR OUT SWING
<b>WIDTH</b>	3'0" MIN, 4'0" MAX
<b>HEIGHT</b>	7'0" MIN, 8'0" MAX
<b>DOOR THICKNESS</b>	1-3/4" ONLY
<b>LOCK PREPS</b>	G15B
<b>UNDERCUT</b>	3/8" MAX.
<b>ASTRAGAL</b>	N/A

*Continued on Page 2*

**HARDWARE**

<b>HINGES</b>	H454 OR H504 -7'0" TO 8'0" <b>MCKINNEY:</b> BUTT HINGES: SP3386, SP3786 HEAVY WEIGHT HINGES <sup>1</sup> OR HEAVY WEIGHT STAINLESS STEEL BTT HINGES CONTINUOUS HINGES: MCK-HG305 <sup>1</sup> <sup>1</sup> THROUGH BOLTED ONLY
<b>LOCKS</b>	<b>CORBIN RUSSWIN:</b> FE6600 <b>SARGENT:</b> FM7300
<b>CLOSERS</b>	<b>CORBIN RUSSWIN:</b> DC8000 <sup>2</sup> <b>NORTON:</b> 7500 <sup>2</sup> <b>SARGENT:</b> 281 <sup>2</sup> <b>YALE:</b> 4400 <sup>2</sup> <sup>2</sup> THROUGH BOLTED ONLY
<b>POWER TRANSFER</b>	SECURITRON: CEPT
<b>DOOR POSITION SWITCH</b>	SECURITRON: DPS-M 3/4
<b>PERIMETER SEALS</b>	PEMKO: MODEL S773 PERIMETER SEAL
<b>RAIN DRIP CAP</b>	PEMKO: MODEL 346 THREAT SIDE MOUNTING ONLY
<b>BOTTOM SWEEP</b>	PEMKO: MODEL 345
<b>THRESHOLD</b>	PEMKO: MODEL 2715
<b>NOTES</b>	ANY ADDITIONAL HARDWARE OPTIONS NEED TO BE APPROVED BY THE FACTORY NO LATCHING SUBSTITUTIONS ALLOWED