



ASSA ABLOY

SARGENT 10 LINE OR YALE 5400 CYLINDRICAL LOCK
 3 MEDECO MAXIM DEADBOLTS
 DESIGN PRESSURE +/- 254 PSF
 TEST PRESSURE +/- 305 PSF
 15 LB. 2X4 @ 100 MPH
PRODUCT QUALIFIED FOR USE IN TORNADO STORM SHELTERS

TEST STANDARDS

ICC	500-2014
FEMA	P320-2014

FRAMES

DESCRIPTION	3F
LABEL	UL WINDSTORM LABEL REQUIRED / NO FIRE LABEL ALLOWED
JAMB DEPTH	4" MINIMUM - SINGLE RABBET; 5-3/4" DOUBLE RABBET, 14" MAXIMUM
PROFILE TYPE	M, G
STEEL GAUGE	16
STEEL TYPE	COLD ROLLED, GALVANEALD
CONSTRUCTION	3F KD OR WELDED
HAND	IN SWING OR OUT SWING
ANCHORS	JAMB MASONRY T, MASONRY WIRE, WPS, OR WELDED TO THE BUILDING STRUCTURE HEAD (HEAD ANCHORING REQUIRED) WPS, OR WELDED TO THE BUILDING STRUCTURE
OVERALL WIDTH	2'10" MIN, 3'2" MAX
OVERALL HEIGHT	6'10" MIN, 7'4" MAX
DOUBLE OPENING	N/A
4" FACE HEAD	ALLOWED
MFG LOCATIONS	CURRIES, CECO OR FLEMMING
STRIKES	E1, THREE E2'S
SILENCERS	ALLOWED
OTHER	

DOORS

FACE TYPE	FLUSH OR GLAZED
GLAZING	TOR-GUARD NBR2, 1.272 FACTORY INSTALLED ONLY
LABEL	UL WINDSTORM LABEL REQUIRED / NO FIRE LABEL ALLOWED
DOOR SERIES	747
DOOR EDGE	CONTINUOUSLY WELDED
STEEL GAUGE	14 GAUGE
STEEL TYPE	COLD ROLLED, GALVANEALD
BEVEL	A
TOP CAP	14 GA. WELDED
HAND	IN SWING OR OUT SWING; GLAZED - IN SWING ONLY
WIDTH	2'8" MIN, 3'0" MAX
HEIGHT	6'8" MIN 7'0" MAX
DOOR THICKNESS	1-3/4" ONLY
LOCK PREPS	G2
UNDERCUT	1/4"
ASTRAGAL	N/A

Continued on Page 2



SARGENT 10 LINE OR YALE 5400 CYLINDRICAL LOCK
 3 MEDECO MAXIM DEADBOLTS
 DESIGN PRESSURE +/- 254 PSF
 TEST PRESSURE +/- 305 PSF
 15 LB. 2X4 @ 100 MPH
PRODUCT QUALIFIED FOR USE IN TORNADO STORM SHELTERS

HARDWARE

HINGES	H453 MCKINNEY: BUTT HINGES: SP3386, SP3786 HEAVY WEIGHT HINGES INCLUDING QC OPTIONS CONTINUOUS HINGES: MCK-HG305 OR MCK-HG305WT10 INCLUDING EPT AND EL OPTIONS MARKAR: CONTINUOUS HINGES: HG305 INCLUDING CPT, EL-8 AND EL-12 OPTIONS
LOCKS	SARGENT: 10 LINE; 3 SARGENT 78-0034-5344 STRIKES; 3 MEDECO MAXIM DEAD BOLT YALE: 5400
CLOSERS	CORBIN RUSSWIN: DC8000 NORTON: 7500 SARGENT: 281 YALE: 4400
POWER TRANSFER DOOR POSITION SWITCH ELECTROMAGNETIC HOLD OPEN	SECURITRON: CEPT SECURITRON: DPS-M 3/4"
MECHANICAL HOLD OPEN	SECURITRON: MODEL 998
PERIMETER SEALS	ROCKWOOD 491S OR 494S
RAIN DRIP CAP	PEMKO: MODEL S773 PERIMETER SEAL
BOTTOM SWEEP	PEMKO: MODEL 346 THREAT SIDE MOUNTING ONLY
THRESHOLD	PEMKO: MODEL 345
VIEWER	PEMKO: MODEL 154, 171, 1715
HARDWARE SUPPLIED WITH THE DOOR	ROCKWOOD 620 AND 622 1-1/2 PR. 4-1/2 X 4-1/2 X .180 MCKINNEY HEAVY WEIGHT HINGES 1 SARGENT 10 LINE LOCK 26D FINISH 3 MEDECO MAXIM DEAD BOLTS 26D FINISH, KEYED ALIKE 3 SARGENT 78-0034 STRIKES FOR MEDECO DEAD BOLTS
NOTES	ANY ADDITIONAL HARDWARE OPTIONS NEED TO BE APPROVED BY THE FACTORY. NO LATCHING SUBSTITUTIONS ALLOWED.